

Polytech network form for PhD Research Grants from the China Scholarship Council

This document describes the PhD subject and supervisor proposed by the French Polytech network of 14 university engineering schools. Please contact the PhD supervisor by email or Skype for further information regarding your application.

Supervisor information	
Family name	AUVITY
First name	Bruno
Email	Bruno.Auvity@univ-nantes.fr
Web reference	http://www.univ-nantes.fr/auvity-b
Lab name	LTEN
Lab web site	http://www.polytech.univ-nantes.fr/ltn/en/
Polytech name	Nantes, thermal and energy sciences department
University name	University of Nantes
Country	France

PhD information	
Title	Recursive identification of continuous-time, non-linear and uncertain dynamic models - application to the diagnosis / prognosis of proton exchange membrane hydrogen fuel cells
Main topics regards to CSC list (3 topics at maximum)	V-5. Energie d'hydrogène et technologie de stockage d'hydrogène Energy of hydrogen and technology of hydrogen storage V-7. Pile à combustible Combustible battery

	I-17. Théorie et technique du contrôle Control theory and technique
Required skills in science and engineering	Electrical Engineering, Electrochemistry, Thermal Science, Mathematics, Numerical Analysis

Subject description (two pages maximum)

Context:

The increasing use of parameterized dynamic models in a wide range of applications (simulation, prediction, control, diagnosis, prognosis) has led to the development of new methods adapted to continuous-time dynamic models identified from input-output discrete-time signals [1-9]. These methods are based on implicit Runge-Kutta ordinary differential equation solvers with controlled estimation error and on maximum likelihood or instrumental variable estimation techniques.

During the last years, the IREENA and LTeN laboratories of the University of Nantes have been collaborating for several years on the integration and diagnosis of hydrogen fuel cells in multi-source systems. The LTeN team is interested in the fine understanding and modeling of the multi-physics phenomena (oxydation-reduction reaction, diffusion and species transport) of the hydrogen cell. The IREENA laboratory is interested in the integration of the energy storage devices such as fuel cells in multi-source and/or propulsive systems and in the real-time identification of the parameters of gray-box-type models.

In a model-based approach to diagnosis, this combination of skills is a real asset for the search for the best model-algorithm pair fitted to the real-time diagnosis and to the prognosis of a system in situation, that is to say taking into account the actual exciting trajectory of the system and desensitization problems of the parameters.

Goals :

The main objective of the thesis is to perform a comparative synthesis of the algorithm-model couples for the diagnosis / prognosis of proton exchange membrane hydrogen fuel cells (PEMFC) used in the 300-kW Energy-Propulsion-System of fluvial shuttles using hybrid (hydrogen and battery) storage. The study will be structured in two distinct parts:

1. State of the art and design of recursive algorithms

The goal is to use of recursive least squares estimators or extended Kalman filters developed in an ongoing thesis, Combining efficient ordinary differential equation solvers and matrix factorization

algorithms. Particular attention will be paid to the algorithmic cost of solutions and its minimization. Whether for an extended Kalman observer or for an identification algorithm minimizing the normalized energy of the output error, we will try to make the most of the knowledge of the sensitivity functions [10] of the model. Their knowledge (simulation) can indeed be used to firstly compare the potential of a model for the diagnosis / prognosis and secondly to avoid a divergence of minimization algorithms when some parameters are momentarily desensitized. The generic character and the relevance of these estimators of physical quantities and of characteristic parameters will then be demonstrated essentially in the case of a real application.

2. Application to the diagnosis / prognosis of the hydrogen fuel cells

There is a wealth of models in the literature for the simulation of PEMFC, but very few can actually be used for real-time fuel cell diagnosis when the exciting trajectory corresponds to a real application case. An indispensable bibliographic synthesis dedicated to gray-box PEMFC models will make it possible to identify some models adapted to our diagnostic / prognosis objectives. Then we will evaluate the performances of model-algorithm pairs for a stack delivering a current corresponding to the power profile generated by a 300 kW Energy Propulsion System fluvial shuttles using hybrid (hydrogen and battery) storage.

References

- [1] H. Garnier, "Direct continuous-time approaches to system identification: overview and benefits for practical applications", *European journal of control*, Vol 24, pp. 50-62, 2015.
- [2] H. Garnier, P. Young (eds.), "Special issue on applications of continuous-time model identification and estimation", *Int. J. Control*, Vol 87, No 7, 2014.
- [3] H. Garnier, L. Wang (eds), "Identification of continuous-time models from sampled data", Springer, coll *Advances in industrial control*, 2008.
- [4] T.P. Bohlin, "Practical Grey-box Process Identification: Theory and Applications", Springer, Coll *Advances in Industrial Control*, 2006.
- [5] P. Frogerais, J. J. Bellanger, L. Senhadji, "Various Ways to Compute the Continuous-Discrete Extended Kalman Filter", *IEEE Transactions on Automatic Control*, Vol 57, No 4, pp. 1000 – 1004, April 2012.
- [6] R.P. Aquilera, B.I. Godoy, J.C. Agüero, G.C. Goodwin, J.I. Yuz, "An EM-based identification algorithm for a class of hybrid systems with application to power electronics", *International Journal of Control*, Vol 87, No 7, pp. 1339-1351, 2014.
- [7] Tomas Menard, « Application de l'homogénéité à la théorie des observateurs non linéaires », thèse de doctorat de l'Ecole Centrale de Nantes, spécialité automatique et informatique appliquée, septembre 2011.
- [8] I. Bouraoui, M. Farza, T. Ménard, R. Ben Abdennour, M. M'Saad, H. Mosrati, "Observer design for a class of uncertain nonlinear systems with sampled outputs –Application to the estimation of kinetic rates in bioreactors", *Automatica*, vol. 55, pp 78-87, May 2015.
- [9] Axel Barrau, "Non-linear state error based extended Kalman filters with applications to navigation", thèse de l'École nationale supérieure des mines de Paris, Spécialité "Informatique temps-réel, robotique et automatique", 15 septembre 2015.
- [10] E. Schaeffer, F. Auger, Z. Shi, P. Guillemet, et L. Loron, « Comparative Analysis of Some Parametric Model Structures Dedicated to EDLC Diagnosis », *IEEE Transactions on Industrial Electronics*, vol. 63, n° 1, pp. 387-396, janv. 2016.
- [11] J. Kim, I. Jeong, K. Nam, J. Yang, T. Hwang, "Sensorless control of PMSM in a high-speed region considering iron loss", *IEEE Trans. on Industrial Electronics*, Vol 62, No 10, pp 6151-6156, oct. 2015.
- [12] W. van Meijl, G. Muisers, A. Borisavljevic, M. Brands, E. Lomonova, "Sensorless observation of a very-high-speed permanent magnet synchronous machine", *Proc. IEEE Int. Symposium on Sensorless Control for Electrical Drives and Predictive Control of Electrical Drives and Power Electronics (SLED/PRECEDE)*, pp. 1-8, oct. 2013.
- [13] H. Rahimi-Eichi, F. Baronti, M. Y. Chow, « Online Adaptive Parameter Identification and State-of-Charge Coestimation for Lithium-Polymer Battery Cells », *IEEE Trans. on Ind. Elect.*, Vol 61, No 4, pp. 2053 – 2061, 2013.
- [14] A. Baba, S. Adachi, "Simultaneous state of charge and parameter estimation of lithium-ion battery using log-normalized unscented Kalman Filter", *IEEE American Control Conference (ACC)*, pp. 311 – 316, 2015.

- [15] C-J Chiang, J-L Yang, W-C Cheng, "Temperature and state-of-charge estimation in ultracapacitors based on extended Kalman filter", *Journal of Power Sources*, Vol. 234, pp. 234-243, 2013.
- [16] A. Eddahech, M. Ayadi, O. Briat, J-M Vinassa, "Online parameter identification for real-time supercapacitor performance estimation in automotive applications", *Electrical Power and Energy Systems*, Vol. 51, pp. 162–167, 2013.