

## Polytech network form for PhD Research Grants from the China Scholarship Council

This document describes the PhD subject and supervisor proposed by the French Polytech network of 14 university engineering schools. Please contact the PhD supervisor by email or Skype for further information regarding your application.

<b>Supervisor information</b>	
<b>Family name</b>	LACROIX
<b>First name</b>	Florian
<b>Email</b>	lacroix@univ-tours.fr
<b>Web reference</b>	<a href="https://cermel.univ-tours.fr/">https://cermel.univ-tours.fr/</a>
<b>Lab name</b>	LaMé Laboratory
<b>Lab web site</b>	<a href="https://www.univ-tours.fr/sciences-et-technologies/laboratoire-de-mecanique-gabriel-lame-lame--116946.kjsp">https://www.univ-tours.fr/sciences-et-technologies/laboratoire-de-mecanique-gabriel-lame-lame--116946.kjsp</a>
<b>Polytech name</b>	Polytech Tours
<b>University name</b>	Tours University
<b>Country</b>	France

<b>PhD information</b>	
<b>Title</b>	Fatigue Behavior of Elastomers used in the aeronautical applications : Innovative approaches using thermal and mechanical signals treatment
<b>Main topics regards to CSC</b>	IV-1 : Nanotechnology and Nanotechnique

<b>list (3 topics at maximum)</b>	IV-6 : Calculation of materials and simulation for design IV-10 : Biomaterials and polymer materials
<b>Required skills in science and engineering</b>	Mechanical Theoretical background

## Subject description (two pages maximum)

Rubbers are widely used in the industry thanks to their ability to undergo large strain and to dampen energy. Consequently, they don't evacuate heat easily, meaning that the temperature of an in service part can reach significant values. This needs to be anticipated as the behavior of those materials is very temperature and time dependent.

One consequence is that rubbers can exhibit self-heating under a mechanical loading without undergoing noticeable damage [Wattrisse et al. 2011] which is mainly caused by the viscoelasticity property of those materials [Meinecke 1991]. The latter depends on the strain rate [Lion 1997], the maximum loading [Cruanes et al. 2013] and the shape of the sample [Ayoub et al. 2012]. Moreover, under suitable conditions and depending of the type of rubber, the strain induced crystallization can be detected by a change in the evolution of the self-heating. However, the influence of the SiC is better observed when working on the thermal sources [Samaca Martinez et al. 2013].

The thermo-mechanical behavior of rubbers during fatigue tests was also investigated. In some cases, the modeling of the evolution of the self-heating was the target: [Boukamel et al. 2001] have proposed a solution of the thermo-mechanical problem using a variational formulation applied to the rheological model of Poynting–Thomson. The later implementation into a FE code achieved its numerical solution [Meo et al. 2002]. Another approach from [Ovalle Rodas et al. 2014] was to develop a large strain thermoviscoelastic constitutive model to describe the self-heating of rubber material low fatigue life tests.

Another way consists in a 0 D approach considered as a way to anticipate the fatigue life when coupled with another technique [Marco et al. 2017]. The thermal measurement would also allow for a rapid determination of the change of the low cycle and high cycle fatigue behaviors [Cruanes et al. 2014], method generalized on rubbers from many studies on other materials (metals) [Doudard et al. 2005] or short fiber reinforced polymer [Jegou et al. 2013] for example).

Based on the previous work of the LaMé team, the aim of the PhD thesis is to consolidate this thermal approach for fatigue by coupling it with other techniques such as signal processing [Hirschberg, 2017] or instrumented indentation [Fradet, 2017].

These approaches will be correlated with microstructure by different observations like SEM or X-Ray Tomography.

The thesis will be managed in the Gabriel LaMé laboratory by means of the research center dedicated to Polymers and Elastomers materials.

[Wattrisse et al. 2011] B. Wattrisse, R. Caborgan, J.-M. Muracciole, L. Sabatier, A. Chrysochoos. Dissipative and coupling effects accompanying the natural rubber elongation. SEM2011, Jun 2011, Uncasville, United States.

[Meinecke 1991] Meinecke E., *Rubber Chemistry and Technology*, 1991, 64, 269 – 284

[Lion 1997] Lion A. , On the large deformation behavior of reinforced rubber at different temperatures. *J. Mech. Phys. Solids* , 1997, 45;1805–1834.

[Cruanes et al. 2013] C Cruanes, G Berton, F Lacroix, JL Poisson, S Méo, N Ranganathan, Study of fatigue behavior of rubber like materials with infrared thermography methods, *Constitutive Models for Rubber VIII*, 2013

[Ayoub et al. 2012] Ayoub, G., Naït-Abdelaziz, M., Zaïri, F., Gloaguen, J.M., Charrier, P., Fatigue life prediction of rubber-like materials under multiaxial loading using a continuum damage mechanics approach: effects of two-blocks loading and R ratio. *Mech. Mater.*, 2012, 52: 87–102.

[Samaca Martinez et al. 2013] Samaca Martinez J.R., Le Cam J.B., Balandraud X., Toussaint E., Caillard J., Mechanisms of deformation in crystallizable natural rubber. Part 1: Thermal characterization, *Polymer*, 2013, 54: 2717-2726

[Boukamel et al. 2001] Boukamel A. , Méo S., Débordes O., Jaeger M., A thermo-viscoelastic model for elastomeric behavior and its numerical application. *Arch. Appl. Mech.*, 2001, 71;785–801.

[Meo et al. 2002] Meo S., Boukamel A., Debordes O., An alysis of a thermoviscoelastic model in large strain. *Comput. Struct.*, 2002, 80; 2085–2098.

[Ovalle Rodas et al. 2014] Ovalle Rodas C., Zaïri F., Naït-Abdelaziz M., A finite strain thermo-viscoelastic constitutive model to describe the self-heating in elastomeric materials during low-cycle fatigue, *Journal of the Mechanics and Physics of Solids*, 2014, 64:396-410

[Marco et al. 2017] Marco Y., Huneau B., Masquelier I., Le Saux V., Charrier P., Prediction of fatigue properties of natural rubber based on the descriptions of the cracks population and of the dissipated energy, *Polymer Testing*, 2017, 59:67-74

[Cruanes et al. 2014] Cruanes C., Berton G., Lacroix F., Méo S., Ranganathan N., Study of the fatigue behaviour of the polychloroprene rubber for uniaxial tests with infrared methods, *Elastomery*, 2014, 18:3-9

[Doudard et al. 2005] DOUDARD C., CALLOCH S., CUGY P., GALTIER A. and HILD F., A probabilistic two-scale model for high-cycle fatigue life predictions, *Fract Engng Mater Struct*, 2005, 28:279-288

[Jegou et al. 2013] Jegou L., Marco Y., Le Saux V. et Calloch S., Fast prediction of the Wöhler curve from heat build-up measurements on Short Fiber Reinforced Plastic, *International Journal of Fatigue*, 2013, 47, 256 –267

[Hirschberg et al., 2017] V. Hirschberg, M. Wilhelm et D. Rodrigue, Fatigue behavior of polystyrene (PS) analyzed from the Fourier transform (FT) of stress response: First evidence of  $I_{2/1}(N)$  and  $I_{2/1}(N)$  as new fingerprints, *Polymer Testing*, 60: 343-350, 2017.

[Fradet et al., 2017] C. Fradet, F. Lacroix, G. Berton, S. Méo, E. Le Bourhis, “Extraction of local mechanical properties of an elastomer by means of nanoindentation : development of protocols and application”, **Matériaux et Techniques**, 105: 109, 2017